

# HYDRAULIC WITH SWEEP

#### MAXIMIZE THE VERSATILITY OF YOUR TOOL CARRIER BY ADDING A STUMP GRINDER





#### **CONTROL THE SWEEP**

Select 3- or 5 hose connection to fit your tool carrier's specification. The sweep is controlled either directly from the tool carrier's controls (5-hose connection) or by an electronic switch box (3-hose connection).



## STABLE SWEEP

All FSI stump grinders with integrated sweep function are built with adjustable sweep speed and two-hydraulic cylinder to secure a stable sweep and equal speed in both directions.



## THE CHOICE IS YOURS

Maximise the versatility of your tool carrier by adding a stump cutter as a tool. The HxxS series comes in 6 variants and is compatible with tool carriers, loaders, and similar ranging from 2 to 3.5 tonnes.



## **WORK AREA**

Grind stumps with difficult access or on slopes. Cover up to 118 cm in one sweep, depending on the model, and efficiently grind away any stump.



#### SIMPLE ATTACHMENT

The stump grinder is attached to the tool carrier using a fixture. As standard it is supplied with an uncoated back plate for welding on a suitable attachment

DATA SHEET FSI-STUMPCUTTERS.COM







## TECHNICAL DATA

## MODEL

|                                    | H20S                          | H2OS-5                                   | H40S <sub>50-75</sub>         | H40S-5 <sub>50-75</sub>                  | H40S <sub>80-110</sub>        | H40S-5 <sub>80-110</sub>                 |
|------------------------------------|-------------------------------|--|-------------------------------|--|-------------------------------|--|
| Recommended excavator size         | 2.0-3.5 ton                   |  |                               |  |                               |  |
| Power requirements (kW/hp)         | 12-22 kW<br>15-30 hp          |  | 18-31 kW<br>25-42 hp          |  | 29-48 kW<br>40-65 hp          |  |
| Oil flow (I/min)                   | 30-50 l/min                   |  | 50-75 l/min                   |  | 80-110 l/min                  |  |
| Oil pressure (max. bar)            | 250 bar                       |  |                               |  |                               |  |
| Connections                        | Pressure, Return,<br>Leak oil | Pressure, Return,<br>Leak oil, 2 x Sweep | Pressure, Return,<br>Leak oil | Pressure, Return,<br>Leak oil, 2 x Sweep | Pressure, Return,<br>Leak oil | Pressure, Return,<br>Leak oil, 2 x Sweep |
| Supplied with hoses                | Yes                           |  |                               |  |                               |  |
| Supplied with hydraulic connectors | Yes                           | No                                       | Yes                           |  | No                            |  |

## **CUTTING HEAD**

|                    | H2OS         | H20S-5   | H40S <sub>50-75</sub> | H40S-5 <sub>50-75</sub> | H40S <sub>80-110</sub> | H40S-5 <sub>80-110</sub> |  |  |
|--------------------|--------------|----------|-----------------------|-------------------------|------------------------|--------------------------|--|--|
| Diameter           | 386 mm       |          | 470 mm                |                         |                        |                          |  |  |
| Teeth / Quantity   | FSI 21       | - 12 pcs | FSI 25 - 16 pcs       |                         |                        |                          |  |  |
| Cutter wheel drive | Direct drive |          |                       |                         |                        |                          |  |  |
| Cutter wheel type  | Staggered    |          |                       |                         |                        |                          |  |  |

## **WORK AREA**

|                    | H2OS     | H2OS-5   | H40S <sub>50-75</sub> | H40S-5 <sub>50-75</sub> | H40S <sub>80-110</sub> | H40S-5 <sub>80-110</sub> |  |
|--------------------|----------|----------|-----------------------|-------------------------|------------------------|--------------------------|--|
| Sweep              | 94 cm    |          | 118 cm                |                         |                        |                          |  |
| Max. cutting depth | 2.5 cm p | er sweep | 5.2 cm per sweep      |                         |                        |                          |  |

## **DIMENSIONS**

|        | H20S   | H20S-5 | H40S <sub>50-75</sub> | H40S-5 <sub>50-75</sub> | H40S <sub>80-110</sub> | H40S-5 <sub>80-110</sub> |  |
|--------|--------|--------|-----------------------|-------------------------|------------------------|--------------------------|--|
| Length | 810 mm |        | 1240 mm               |                         |                        |                          |  |
| Width  | 690 mm |        | 800 mm                |                         |                        |                          |  |
| Height | 580    | mm     | 720 mm                |                         |                        |                          |  |
| Weight | 92     | kg     | 200                   | ) kg                    | 25                     | 0 kg                     |  |

FSI Stump Cutters reserves the right to make changes in engineering, design, and specifications without notice. Dimensions may vary, depending on options and selections. Vers: 11 - 2023

**FSI-STUMPCUTTERS.COM**